

ASPIFLOC® 50 EC



Fountain wash and contaminated water treatment of paint, inks, degreasing agent and hot water.



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)

Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69 - contact@aspifloc.com - www.aspifloc.com

ASPIFLOC® 50 EC

Fountain wash and contaminated water treatment of paint, inks, degreasing agent and hot water.

ADVANTAGES

- Compact multifunction station : Washing Sink - Water held at a temperature of 45 ° C
- effluent treatment
- water reuse after treatment
- Usable on effluent which require hot water for washing
- Minimum cost of operations
- low investment

SPECIFICATIONS

- 1 Perforated over the sink washing tray
- 1 Wash brush
- 1 Gun for drying compressed air
- 1 Perforated filter with filter Pocket tank
- 1 Stainless steel tray on castors with drain valve for recovery of treated and filtered water
- Size:
 - Length : 800 mm
 - Width : 600 mm
 - Height : 1300 mm
 - Weight : 65 kg
 - Tank : 50 liters
- Mixer:
 - Pneumatic
- Power supply:
 - City water
 - Compressed air

OPTIONS

- Front door base



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)
Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69
contact@aspifloc.com - www.aspifloc.com