

ASPIFLOC® 50 EF



**Fountain of washing and treatment of mud of paint,
inks, degreasing agent and cold water.**



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)

Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69 - contact@aspifloc.com - www.aspifloc.com

ASPIFLOC® 50 EF

Fountain of washing and treatment of mud of paint, inks, degreasing agent and cold water.

ADVANTAGES

- Simple to use
- Possibility of reuse of effluent = zero discharge
- Small footprint
- Sturdiness

SPECIFICATIONS

- 1 Perforated over the sink washing tray
- 1 Wash brush
- 1 Gun for drying compressed air
- 1 Perforated filter with filter Pocket tank
- 1 Stainless steel tray on castors with drain valve for recovery of treated and filtered water
- Size:
 - Length: 800 mm
 - Width: 600 mm
 - Height : 1300 mm
- Weight: 65 kg
- Tank: 50 liters
- Mixer: Pneumatic
- Power supply:
 - City water
 - Compressed air

OPTIONS

- Front door base



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)
Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69
contact@aspifloc.com - www.aspifloc.com