

ASPIFLOC® TS SKIMMER HP2



Complete degreasing machine with multiple filtration & treatment water holding tanks. Zero discharge and constant filtration ensuring highest quality degrease/phosphating.



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)

Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69 - contact@aspifloc.com - www.aspifloc.com

ASPIFLOC® TS SKIMMER HP2

Water treatment plant at high pressure washing



ADVANTAGES

- Reduce water consumption by over 95% when compared with standard degreasing tunnels.
- 90% reduction in degreasing/phosphate chemical consumption.
- Elimination of pollution during the degreasing of parts before repair before painting.
- Fully automatic system.
- Quick return on investment.

SPECIFICATIONS

- Electricity: Mono - 220/240 Volts - 15 Amps.
- Compressed Air - 5BAR
- Sizes : Length : 3230 mm x Width : 1680 mm x Height : 1213 mm
- Weight : 390 kg
- Tank : 750-liters

OPTIONS

- Additional filters/rinse to give 400+ hours s/s test.
- Automatic dosing option



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)
Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69
contact@aspifloc.com - www.aspifloc.com