

ASPIFLOC® TS SKIMMER



Central decontamination, hydrocarbons, oils on bath area treatment electroplating bath, mineral laden effluent, etc ...



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)

Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69 - contact@aspifloc.com - www.aspifloc.com

ASPIFLOC®TS SKIMMER

Central decontamination, hydrocarbons, oils on bath area treatment
electroplating bath, mineral laden effluent, etc ...



ADVANTAGES

- Consistent quality of cleaning and degreasing
- Reduction of approximately 30% in the consumption of treatment chemicals
- Treatment bath lifetime increased by upto 3 times and more.
- Sharp decline in cleaning and maintenance of the installation costs.

SPECIFICATIONS

- Capacity of purification of fluids with a viscosity of 40 cst ... 90 to 120 liters per minute
- Working temperature:... 5 to 70 ° C
- PH range ... 0 to 15
- Dimension of the carpet ... 700 mm x 1000 mm
- Size:
 - Length : 970 mm
 - Width : .300 mm
 - Height : 500 mm
- Capacity of the tray to sludge: 190 liters
- Quality of the filtering system: STAINLESS STEEL 304
- Quality of the chassis: STEEL painting EPOXY
- Electric power: 0.19 kw
- Flow of the pumps in liters per minute: 76 liters/minute to 1,5 Bars
- Maximum size in mm for the pumps: 6.5 mm
- Consumption one pump in compressed air at 2 bars: 60 liters per minute to 1,5 Bars



L'innovation au service de l'environnement

SPCB - ZI KERMELIN Nord, 28 rue Lavoisier, 56890 Saint Avé (France)
Tél : + 33 (0) 297 60 82 82 - Fax : + 33 (0) 297 60 85 69
contact@aspifloc.com - www.aspifloc.com